

Pneumatic cylinders			Linear cylinder			Lifting cylinder			Linear rail slide				
PZ32-25	PZ32-50	PZ32-80	PZ32-100	PZ32-125	PZ32-160	PZ32-200	PZ32-25D	PZ32-50D	PZ32-80D	PZ32-100D	PZ32-125D	PZ32-160D	PZ32-200D



Pneumatic cylinders

(with thru bore piston rod)

Advantages, benefits, comparisons and tips!
Stacks of information all about this product are on page 317.

Sommer-automatic
Grippers
Separators
Swivel units
Rotating jaws
Axial compensators
Tool changers
Linear cylinders
Shock absorbers
Rotary cylinders
Air vane motors
Vacuum components
Accessories
Quick finder



Order no.:			
PZ32-25D	PZ32-50D	PZ32-80D	
Stroke [mm]:			
25	50	80	
Extension force, max. [N]:			
340	340	340	
Retraction force, max. [N]:			
340	340	340	
Min. running speed [m/s]:			
0,02	0,02	0,02	
Max. running speed [m/s]:			
0,6	0,6	0,6	
Air volume per cycle [cm³]:			
30	60	96	
Min./max. operating temperature [°C]:			
5/80	5/80	5/80	
Temp. resistant version up to 150° C [addition when ordering]:			
T2	T2	T2	
Weight [kg]:			
0,5	0,7	0,8	

All data measured at 6 bar.

See Page 317 for Accessory list.

